



Seal Coat® Clear Urethane Coating, 11 Wt Oz
 No. 18411 | Item# 1005238 | Case# 1005237

Product Description	It provides a conformal polyurethane coating that insulates electrical equipment and seals out water and moisture. This product allows clear visualization of whatever it is sprayed upon. It is an excellent insulator of PC boards, since it allows visualization of circuit paths. It dries quickly to a hard, durable, flexible film.
Color	Clear
Applications	On motor windings, terminals, bus bars, commutator ends, stator coils, and PC boards
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Urethane Coating
Net Fill	11 Wt Oz
UPC Code	078254184111
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.6H x 8.4W x 11.3D in
Cases Per Pallet	133
Case Weight	11 lbs
I 2 of 5 Code	30078254184112
Appearance	Clear Viscous Liquid
Flash point (F)	-4°F
Flash point (C)	-20°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.717
Plastic Safe	Yes
Evaporation Rate	Moderate
Dry Time - Fully Dry	72 Hours
Dry Time - Tack Free	15 to 30 Minutes
Coverage	20 to 25 Sq Ft

Last revised: 4/30/2020
 Page 1 of 2





Dielectric Strength	3,000 Volts/Mil
Working Temp (F)	-90 to 250°F
Working Temp (C)	-67.8 to 121.1°C
Propellant	Hydrocarbon
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	63.9
VOC g/L (Consumer Product def)	457.8
VOC lbs/gal (Consumer Prod def)	3.8
VOC Category	Aerosol Coating: Electrical Coating
MIR Limit (EPA)	None
MIR Limit (CA)	2.0
MIR Value	1.46
Removal (How To)	Extremely difficult to remove, scraping is recommended.