



Seal Coat® Clear Urethane Coating, 11 Wt Oz
 No. 18411 | Item# 1005238 | Case# 1005237

Product Description

It provides a conformal polyurethane coating that insulates electrical equipment and seals out water and moisture. This product allows clear visualization of whatever it is sprayed upon. It is an excellent insulator of PC boards, since it allows visualization of circuit paths. It dries quickly to a hard, durable, flexible film.

Color

Clear

Applications

On motor windings, terminals, bus bars, commutator ends, stator coils, and PC boards

Unit Package Description

16 Ounce Aerosol

Brand

CRC

Generic Description 1

Urethane Coating

Net Fill

11 Wt Oz

UPC Code

078254184111

Unit Dimensions

7.75H x 2.63W x 2.63D in

Units Per Case

12

Case Dimensions

8.6H x 8.4W x 11.3D in

Cases Per Pallet

133

Case Weight

11 lbs

I 2 of 5 Code

30078254184112

Appearance

Clear Viscous Liquid

Flash point (F)

-4°F

Flash point (C)

-20°C

Flammability Class - CPSC

Extremely Flammable

Spec Gravity Concentrate

0.717

Plastic Safe

Yes

Evaporation Rate

Moderate

Dry Time - Fully Dry

72 Hours

Dry Time - Tack Free

15 to 30 Minutes

Coverage

20 to 25 Sq Ft

Last revised: 4/30/2020

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t i n • 800-272-8963 • crcindustries.com



Dielectric Strength	3,000 Volts/Mil
Working Temp (F)	-90 to 250°F
Working Temp (C)	-67.8 to 121.1°C
Propellant	Hydrocarbon
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	63.9
VOC g/L (Consumer Product def)	457.8
VOC lbs/gal (Consumer Prod def)	3.8
VOC Category	Aerosol Coating: Electrical Coating
MIR Limit (EPA)	None
MIR Limit (CA)	2.0
MIR Value	1.46
Removal (How To)	Extremely difficult to remove, scraping is recommended.