



**Zinc-It® Instant Cold Galvanize, 13 Wt Oz**  
 No. 18412 | Item# 1005240 | Case# 1005239

Product Description	High-performance coating of >93% pure zinc that electrochemically bonds with ferrous metals to form a galvanic cell. It actively fights rust and corrosion. Use as a touch-up for damaged galvanized coatings. Dries quickly. Outdoor protection: 1-2 years.
Applications	On threads, exposed edges, fasteners, conduit, strapping, welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste containers, catwalks, and guard rails. Meets ASTM A780
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Instant Cold Galvanized Coating
Net Fill	13 Wt Oz
UPC Code	078254184128
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.69H x 8.44W x 11.31D in
Cases Per Pallet	75
Case Weight	14 lbs
I 2 of 5 Code	30078254184129
Appearance	Gray Viscous Liquid
Flash point (F)	-2°F
Flash point (C)	-19&#176;C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.77 to 0.85
Plastic Safe	Yes
Dry Time - Fully Dry	8 Hours
Dry Time - Tack Free	20 Minutes
Recoat	Before 1 Hour or After 48 Hours
Coverage	24 Sq Ft at 1 Mil Dry

Last revised: 1/8/2020  
 Page 1 of 2





Working Temp (F)	130°F (Continuous) / 150°F (Intermittent)
Working Temp (C)	54.4°C (Continuous) / 65.6°C (Intermittent)
Propellant	Hydrocarbon
Aerosol Flammability Level	III
Military Specification Number	Meets requirements of Mil-P-26915, Meets requirements of Mil-P-46105, Meets requirements of Mil-P-21035B
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	45.6
VOC g/L (Consumer Product def)	555.6
VOC lbs/gal (Consumer Prod def)	4.64
VOC Category	Aerosol Coating: Metallic
MIR Limit (EPA)	1.9
MIR Limit (CA)	1.25
MIR Value	1.2
Removal (How To)	Remove with aromatic solvents, Xylene. Toluene can be used, but is not recommended.