



## Zinc-It® Instant Cold Galvanize, 13 Wt Oz No. 18412 | Item# 1005240 | Case# 1005239

Product Description High-performance coating of >93% pure zinc that

electrochemically bonds with ferrous metals to form a galvanic cell. It actively fights rust and corrosion. Use as a touch-up for damaged galvanized coatings. Dries quickly.

Outdoor protection: 1-2 years.

Applications On threads, exposed edges, fasteners, conduit, strapping,

welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste containers, catwalks, and guard rails. Meets ASTM A780

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Instant Cold Galvanized Coating

Net Fill 13 Wt Oz

UPC Code 078254184128

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.69H x 8.44W x 11.31D in

Cases Per Pallet 75
Case Weight 14 lbs

I 2 of 5 Code 30078254184129
Appearance Gray Viscous Liquid

Flash point (F) -2°F

Flash point (C) -19&#176: C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.77 to 0.85

Plastic Safe Yes

Dry Time - Fully Dry 8 Hours
Dry Time - Tack Free 20 Minutes

Recoat Before 1 Hour or After 48 Hours

Coverage 24 Sq Ft at 1 Mil Dry

Last revised: 1/8/2020

Page 1 of 2







Working Temp (F) 130°F (Continuous) / 150°F (Intermittent)
Working Temp (C) 54.4°C (Continuous) / 65.6°C (Intermittent)

Propellant Hydrocarbon

Aerosol Flammability Level III

Military Specification Meets requirements of Mil-P-21035B, Meets requirements

Number of Mil-P-26915, Meets requirements of Mil-P-46105

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

4.64

VOC % (Consumer Product 45.6

def)

VOC g/L (Consumer 555.6

Product def)

VOC lbs/gal (Consumer

Prod def)

VOC Category Aerosol Coating: Metallic

MIR Limit (EPA) 1.9
MIR Limit (CA) 1.25
MIR Value 1.2

Removal (How To) Remove with aromatic solvents, Xylene. Toluene can be

used, but is not recommended.

Last revised: 1/8/2020

Page 2 of 2

