



## Zinc-It® Instant Cold Galvanize™ Zinc Rich Galvanize Coating, 1 Gal

No. 18413 | Item# 1005241 | Case# 1005241

Product Description	High-performance coating of >92% pure zinc that electrochemically bonds with ferrous metals to form a galvanic cell. It actively fights rust and corrosion. Use as a touch-up for damaged galvanized coatings. Dries quickly. Outdoor protection: 1 - 2 years
Applications	On threads, exposed edges, fasteners, conduit, strapping, welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste containers, catwalks, and guard rails.
Unit Package Description	1 Gallon Can
Brand	CRC
Generic Description 1	Instant Cold Galvanized Coating
Net Fill	1 Gal
UPC Code	078254184135
Unit Dimensions	7.88H x 8W x 8D in
Units Per Case	1
Case Dimensions	9.8H x 9.4W x 9.1D in
Cases Per Pallet	60
Case Weight	22 lbs
I 2 of 5 Code	30078254184136
Appearance	Gray Viscous Liquid
Flash point (F)	45°F
Flash point (C)	7°C
Flammability Class - CPSC	Flammable
Spec Gravity Concentrate	2.47
Plastic Safe	May Harm Sensitive Plastics
Evaporation Rate	Slow
Dry Time - Fully Dry	72 Hours
Dry Time - Tack Free	30 Minutes

Last revised: 1/8/2020

Page 1 of 2



**Chemical Solutions to Keep You Moving™**

f t+ d+ in m • 800-272-8963 • [crcindustries.com](http://crcindustries.com)

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Recoat	8 Hours
Coverage	674 Sq Ft at 1 Mil Dry
Working Temp (F)	250 to 300°F (Continuous), Up to 450°F (Intermittent)
Working Temp (C)	121.1 to 148.9°C (Continuous), 232.2°C (Intermittent)
Propellant	None
Military Specification Number	Meets requirements of Mil-P-26915, Meets requirements of Mil-P-46105
DOT Proper Shipping Name	Paint, Limited Quantity
VOC % (Consumer Product def)	19.95
VOC g/L (Consumer Product def)	493.36
VOC lbs/gal (Consumer Prod def)	4.11
VOC Category	Not Regulated - (Not for field application)
Removal (How To)	Paint stripper or other solvent