



## Copper Coat® Gasket Compound, 4 FI Oz

No. 401504 | Item# 1006075 | Case# 1006074

**Product Description** High temperature, high quality gasket sealer. Prevents

compression loss on paper, cork and premium gaskets. Dauber built into the lid for easy application and storage.

**Applications** Automatic transmissions, cover plates, diesel heads, high

compression engines, hi-speed turbine superchargers,

hydraulic pumps

Unit Package Description 4 ounce Brush Top Bottle

**Brand** K&W

Generic Description 1 Gasket Compound

Net Fill 4 FI Oz

**UPC** Code 078372015045

**Unit Dimensions** 2.75H x 2.5W x 2.5D in

Units Per Case 12

Case Dimensions 3.7H x 6.8W x 8D in

Cases Per Pallet 280 Case Weight 5 lbs

I 2 of 5 Code 10078372015042

**Appearance** Viscous Copper Liquid

30°F Flash point (F) -1.1°C Flash point (C)

Flammability Class - CPSC Flammable

Spec Gravity Concentrate 0.76 Plastic Safe Yes

**Evaporation Rate** Moderate

Dielectric Strength Not Determined Working Temp (F) -80 to 400°F

Working Temp (C) -62.2 to 204.4°C

Propellant None

**DOT Proper Shipping Name** Heptanes mixture, Limited Quantity

Last revised: 3/31/2020

Page 1 of 2







VOC % (Consumer Product 74.2 def)

VOC q/L (Consumer 549

VOC g/L (Consumer 54 Product def)

VOC lbs/gal (Consumer 4.57 Prod def)

VOC Category Not Regulated
Removal (How To) Gasket remover

Last revised: 3/31/2020

Page 2 of 2

