



Copper Coat® Gasket Compound, 4 FI Oz

No. 401504 | Item# 1006075 | Case# 1006074

Product Description High temperature, high quality gasket sealer. Prevents

compression loss on paper, cork and premium gaskets. Dauber built into the lid for easy application and storage.

Applications Automatic transmissions, cover plates, diesel heads, high

compression engines, hi-speed turbine superchargers,

hydraulic pumps

Unit Package Description 4 ounce Brush Top Bottle

Brand K&W

Generic Description 1 Gasket Compound

Net Fill 4 Fl Oz

UPC Code 078372015045

Unit Dimensions 2.75H x 2.5W x 2.5D in

Units Per Case 12

Case Dimensions 3.7H x 6.8W x 8D in

Cases Per Pallet 280
Case Weight 5 lbs

I 2 of 5 Code 10078372015042

Appearance Viscous Copper Liquid

Flash point (F) 30° F Flash point (C) -1.1° C

Flammability Class - CPSC Flammable

Spec Gravity Concentrate 0.76
Plastic Safe Yes

Evaporation Rate Moderate

Dielectric Strength

Working Temp (F)

Working Temp (C)

Not Determined

-80 to 400°F

-62.2 to 204.4°C

Propellant None

DOT Proper Shipping Name Heptanes mixture, Limited Quantity

Last revised: 3/31/2020

Page 1 of 2







VOC % (Consumer Product 74.2 def)

VOC q/L (Consumer 549

VOC g/L (Consumer 54 Product def)

VOC lbs/gal (Consumer 4.57 Prod def)

VOC Category Not Regulated
Removal (How To) Gasket remover

Last revised: 3/31/2020

Page 2 of 2

