



Clear Urethane Seal Coat, 312 Grams No. 72049 | Item# 1006120 | Case# 1006119

Product Description Polyurethane coating that insulates electrical equipment

and seals out water and moisture. The clear formula

allows for visualization of equipment.

Applications On motor windings, terminals, bus bars, commutator

ends, stator coils, and PC boards

Unit Package Description 16 Ounce (473 ml) Aerosol

Brand CRC

Generic Description 1 Urethane Coating

Net Fill 312 Grams

UPC Code 078254720494

Unit Dimensions 19.69H x 6.68W x 6.68D cm

Units Per Case 12

Case Dimensions 21.84H x 21.33W x 28.7D cm

Cases Per Pallet 133
Case Weight 4.98 kg

I 2 of 5 Code 30078254720495 Appearance Clear Viscous Liquid

Flash point (F) -4°C
Flash point (C) -20°C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.717
Plastic Safe Yes
Evaporation Rate Fast

Dry Time - Fully Dry 72 Hours

Dry Time - Tack Free 10 Minutes

Recoat 72 Hours

Coverage 6.1 to 7.6 Sq M

Dielectric Strength 3,000 Volts/Mil

Working Temp (F) -90 to 250°F

Last revised: 2/13/2019

Page 1 of 2







Working Temp (C) -67.8 to 121.1°C

Propellant Hydrocarbon

Aerosol Flammability Level III

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

Restricted from Sale In: Not for sale in United States.

Removal (How To) Extremely difficult to remove, scraping is recommended.

Last revised: 2/13/2019

Page 2 of 2

