



Power Lube w/PTFE, 312 Grams No. 73045 | Item# 1006154 | Case# 1006153

Product Description Contains PTFE for long-lasting lubrication and protection

from friction, wear and corrosion. Helps to increase the operating efficiency of parts and equipment. Can

withstand extreme load carrying situations.

Applications Bearings, gears, linkages, motors, chains, cables, rollers,

guide bars, pulleys, cams, valves, ball joints, hinges, slides, cutting tools, taps, dies, pistons, handling equipment, conveyors, hoists, lifts, doors and fans.

Unit Package Description 16 Ounce (473 ml) Aerosol

Brand CRC

Generic Description 1 High Performance Lubricant with PTFE

Net Fill 312 Grams

UPC Code 078254730455

Unit Dimensions 19.69H x 6.68W x 6.68D cm

Units Per Case 12

Case Dimensions 20.57H x 21.08W x 28.19D cm

Cases Per Pallet 133

Case Weight 5.44 kg

I 2 of 5 Code 30078254730456

Appearance Light Amber Liquid w/white precipitate

Base Type Petroleum Solvent

Flash point (F) <20°F Flash point (C) <-6.7°C

Flammability Class - CPSC Extremely Flammable

Plastic Safe No Film Type Wet

Film Thickness Not Determined

Evaporation Rate Fast

Dielectric Strength Not Determined
Working Temp (F) Max 300°F

Last revised: 9/4/2020

Page 1 of 2







Working Temp (C) Max 148.9°C

Propellant Carbon Dioxide

NSF Category Code H2

NSF Number 154239

Aerosol Flammability Level II

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

Removal (How To) Remove with petroleum solvents or mineral spirits.

Last revised: 9/4/2020

Page 2 of 2

