



Sta-Plex™ Extreme Pressure Premium Red Grease, 396 Grams

No. 73190 | Item# 1006188 | Case# 1006187

| | |
|---------------------------|---|
| Product Description | A superior multi-purpose certified lithium complex based NLGI #2 grease. Contains extreme pressure, anti-wear, & anti-oxidation additives. Ideal for high temperature & performance applications. Drop point 500°F |
| Applications | Ind. mining, metal production, machining, plastic molding, pumps, electric motors, ball & roller bearings, kilns, assembly plants, drying ovens, trucks, automobiles, buses, construction equipment, off-road operations, tractors mowers, reapers, water pumps |
| Unit Package Description | 14 Ounce (414 ml) Cartridge |
| Brand | CRC |
| Generic Description 1 | Premium Red Grease |
| Net Fill | 396 Grams |
| UPC Code | 078254731902 |
| Unit Dimensions | 23.65H x 5.41W x 5.41D cm |
| Units Per Case | 10 |
| Case Dimensions | 24.13H x 11.43W x 28.9D cm |
| Cases Per Pallet | 150 |
| Case Weight | 4.99 kg |
| I 2 of 5 Code | 30078254731903 |
| Appearance | Red Semi-Solid to Solid Grease |
| Base Type | Lithium Complex |
| Flash point (F) | 475°F |
| Flash point (C) | 246.1°C |
| Flammability Class - CPSC | None |
| Spec Gravity Concentrate | 0.9 |
| NLGI Grade | 2 |
| Timken OK Load Lbs. | 80 Lbs |
| Plastic Safe | Not Determined |

Last revised: 2/13/2020
Page 1 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



| | |
|--------------------------|---|
| Evaporation Rate | Slow |
| Dielectric Strength | Not Determined |
| Working Temp (F) | 0 to 400°F (300°F continuous) |
| Working Temp (C) | -17.8 to 204.4°C 149°C continuous) |
| 4 Ball EP | 70 LWI; weld point 500+ |
| 4 Ball Wear | 0.4 typical |
| Drop Point | 260+ °C |
| Elastomer Compatibility | 0 to 30% vol; 0 to 15 hard |
| Leakage | Not Determined |
| Low Temp Torque | 15.5 Max |
| Oil Separation | 5% Typical |
| Oxidation Stability | Not Determined |
| Pour Point (F) | 5°F |
| Pour Point (C) | -15°C |
| ISO Viscosity Grade | 220 |
| Water Washout | 5% typical |
| Worked Penetration | 265 to 295 |
| Propellant | None |
| DOT Proper Shipping Name | Not Regulated |
| Restricted from Sale In: | Not for sale in United States. |
| Removal (How To) | Remove with a degreaser or brake cleaner product. |

Last revised: 2/13/2020
Page 2 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.