

Thread Lubricant, 226 Grams (Discontinued)

No. 73925 | Item# 1006215 | Case# 1006214

Product Description A general purpose lubricant that prevents the seizing and

galling of threaded surfaces caused by corrosion. Safe for

use on ferrous and non-ferrous metals.

Applications For use on aluminum conduit, bolts, bushings, fittings,

flanges, nuts, pipes, plugs and screws.

Product Discontinued Unit Package Description 8 Ounce (237 ml) Bottle

Brand CRC

Generic Description 1 Thread Lubricant

Net Fill 226 Grams

UPC Code 078254739250

Unit Dimensions 10.8H x 6.35W x 6.35D cm

Units Per Case 6

Case Dimensions 12.45H x 10.92W x 18.42D cm

Cases Per Pallet 315
Case Weight 1.82 kg

I 2 of 5 Code 30078254739251

Appearance Amber Semi-Solid to Solid Grease

Base Type Lithium

Flash point (F) 334°F

Flash point (C) 167.8°C

Flammability Class - CPSC None

Spec Gravity Concentrate 0.9

Plastic Safe Not Determined

Film Type Grease

Evaporation Rate Very Slow

I SO Viscosity Grade 150 NLGI Grade 2

Working Temp (F) 0 to 300°F

Working Temp (C) -17.8 to 148.9°C

Last revised: 5/20/2019

Page 1 of 2





Propellant None

DOT Proper Shipping Name Not Regulated

Restricted from Sale In: Not for sale in United States.

Removal (How To) Remove with a degreaser or brake cleaner product.

Product Discontinued

Last revised: 5/20/2019

Page 2 of 2

