



Zinc Mate™, 368 Grams

No. 75054 | Item# 1006311 | Case# 1006310

Product Description Coating of >93% pure zinc actively fights rust and

corrosion. Use as a touch-up for damaged galvanized

coatings. Dries quickly.

Applications Threads, exposed edges, fasteners, conduit, strapping,

welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste containers, catwalks, and quard rails. Meets ASTM A780

Unit Package Description 16 Ounce (473 ml) Aerosol

Brand CRC

Generic Description 1 Instant Cold Galvanized Coating

Net Fill 368 Grams

UPC Code 078254750545

Unit Dimensions 23.5H x 6.68W x 6.68D cm

Units Per Case 12

Case Dimensions 20.95H x 21.26W x 27.94D cm

Cases Per Pallet 75

Case Weight 6.8 kg

I 2 of 5 Code 30078254750546

Appearance Gray Viscous Liquid

Flash point (F) -2°F

Flash point (C) -19°C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.77 to 0.85

Plastic Safe Yes

Evaporation Rate Fast

Dry Time - Fully Dry 8 Hours

Dry Time - Tack Free 20 Minutes

Recoat Before 1 Hour or After 48 Hours

Coverage 2.6 to 3.0 Sq M at 3 Mils Dry

Working Temp (F) 130°F (Continuous) / 150°F (Intermittent)

Last revised: 3/27/2020

Page 1 of 2







Working Temp (C) 54.4°C (Continuous) / 65.6°C (Intermittent)

Propellant Hydrocarbon

Aerosol Flammability Level III

Military Specification Meets requirements of Mil-P-26915, Meets requirements of

Number Mil-P-46105

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

Restricted from Sale In: Not for sale in United States.

Removal (How To) Remove with aromatic solvents, Xylene. Toluene can be

used, but is not recommended.

Last revised: 3/27/2020

Page 2 of 2

