

## Silaramic® Brake System Grease, 255 Grams (Discontinued) No. 75363 | Item# 1006387 | Case# 1006386

**Product Description** A synthetic, dry-film, ceramic lubricant formulated to

reduce brake noise and vibrations by dampening all brake vibrating frequencies. Will not run off or wash out. Works in extreme temp ranges from -50 to 3000°F. Protects

against uneven pad wear.

**Applications** 

All brake systems and brake components, including calipers, bushings, holes, pins, inserts, anchors, bolts,

calipers and boots

255 Grams

Unit Package Description

9 Ounce (266 ml) Tub With Brush

Brand

Net Fill

Product

Discontinued

**CRC** 

Generic Description 1 Brake Caliper Synthetic Grease

**UPC** Code

078254753638

**Unit Dimensions** 10.8H x 9.86W x 9.86D cm

Units Per Case 12

Case Dimensions 12.7H x 31.11W x 40.64D cm

Cases Per Pallet

Case Weight 3.63 kg

I 2 of 5 Code 30078254753639

Appearance Off White Semi Solid Grease

Base Type Polydimethylsiloxane

Flash point (F) 550°F 287.8°C Flash point (C) Flammability Class - CPSC None Spec Gravity Concentrate 1.0

NLGI Grade

Timken OK Load Lbs. Not Determined

Plastic Safe Yes

**Evaporation Rate** Very Slow

Dielectric Strength Not Determined

Last revised: 1/16/2019

Page 1 of 2





## Product Discontinued

Working Temp (F) -50 to 3000°F

Working Temp (C) -45.6 to 1648.89°C

4 Ball EP Not Determined
4 Ball Wear Not Determined

Drop Point None

Elastomer Compatibility Compatible

Leakage 0.2

Low Temp Torque Not Determined

Oil Separation 0.2
Oxidation Stability Yes
Water Washout 0.25

Worked Penetration 265 to 295

Propellant None

DOT Proper Shipping Name Not Regulated

Restricted from Sale In: Not for sale in United States.

Removal (How To) Remove with petroleum solvents.

Last revised: 1/16/2019

Page 2 of 2

