



Cutting Oil Thread Cutting Lubricant, 340 Grams

No. 75500 | Item# 1006395 | Case# 1006394

Product Description

Cutting Oil is a superior thread cutting lubricant for use on all types of metals, including brass, copper and aluminum.

Applications

Tapping, threading, drilling, sawing, shearing, turning, and reaming metal parts, pipes, conduit, screws, bolt holes, housings, aluminum sheets, strapping, gears and chains.

Unit Package Description

16 Ounce (473 ml) Aerosol

Brand

CRC

Generic Description 1

Thread Cutting Lubricant

Net Fill

340 Grams

UPC Code

078254755007

Unit Dimensions

19.69H x 6.68W x 6.68D cm

Units Per Case

12

Case Dimensions

20.57H x 21.08W x 28.19D cm

Cases Per Pallet

133

Case Weight

5.44 kg

I 2 of 5 Code

30078254755008

Appearance

Clear Dark Amber Liquid

Base Type

Petroleum

Flash point (F)

>300°F

Flash point (C)

>149°C

Flammability Class - CPSC

Flammable

Spec Gravity Concentrate

0.9244

Plastic Safe

Safe on Most

Film Type

Non-Drying

Film Thickness

Not Determined

Evaporation Rate

Slow

Dielectric Strength

Not Determined

Working Temp (F)

Max 300°F

Last revised: 3/18/2021

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Working Temp (C)	Max 148.9°C
Propellant	Hydrocarbon
NSF Category Code	P1
NSF Number	154095
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
Restricted from Sale In:	Not for sale in United States.
Removal (How To)	Remove with general purpose degreaser.

