



Marine Fuel Stabilizer - Gasoline, 236 Milliliters

No. 76062 | Item# 1006417 | Case# 1006416

Product Description

A concentrated, high-potency formula that keeps stored gas fresh for easy start-up next season & optimum performance year round. Prevents harmful fuel separation caused by Ethanol-blended gasoline. Protects against gum & resin build-up.

Applications

All 2 and 4 cycle gasoline engines, marine engines, agricultural equipment, lawn & garden equipment, automobiles, chainsaws, generators, jet skis, lawn mowers, motorcycles, snow blowers, snowmobiles, tractors

Unit Package Description

8 Ounce (236 ml) Bottle

Brand

CRC (Canada)

Generic Description 1

Marine Fuel Stabilizer-Gasoline

Net Fill

236 Milliliters

UPC Code

078254760629

Unit Dimensions

15.24H x 4.14W x 9.35D cm

Units Per Case

12

Case Dimensions

21.33H x 18.54W x 32D cm

Cases Per Pallet

120

Case Weight

4.08 kg

I 2 of 5 Code

30078254760620

Appearance

Red Liquid

Base Type

Petroleum Distillate

Flash point (F)

129.2°F

Flash point (C)

54°C

Flammability Class - CPSC

Flammable

Spec Gravity Concentrate

0.78

Plastic Safe

Not Determined

Evaporation Rate

Moderate

Dielectric Strength

Not Determined

Working Temp (F)

-40 to 100°F

Last revised: 11/15/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Working Temp (C)	-40 to 37.8°C
Propellant	None
Aerosol Flammability Level	Not Applicable
DOT Proper Shipping Name	Petroleum Distillates, N.O.S., Limited Quantity
Restricted from Sale In:	No State Restrictions
Treatment Ratio	30 ml (1 oz) treats 9 L (2.5 gal) of gasoline or 38 L (10 gal) of diesel fuel.