

South Africa 2-26® Multi-Purpose Lubricant, 312 Grams (Discontinued)

No. 92005 | Item# 1006872 | Case# 1006871

Product Description Plastic safe lubricant, penetrant and corrosion inhibitor

that helps prevent electrical malfunctions caused by water penetration, humidity, condensation or corrosion. Restores

resistance values and helps stop current leakage.

Applications Connectors, relays, circuit breakers, transformers,

switchgear, motors, generators, controls, instruments, communication assemblies, electronics, alarm systems, starters, tubing, castings, gears, weld rod, wire, fixtures,

dies, jigs, shim stock, chucks.

Unit Package Description 16 Ounce (473 ml) Aerosol

Brand CRC (South Africa)

Generic Description 1 Lubricant and Penetrant

Net Fill 312 Grams

UPC Code 078254920054

Unit Dimensions 19.69H x 6.68W x 6.68D cm

Units Per Case 12

No Photo

Available

Case Dimensions 20.57H x 21.08W x 28.19D cm

Cases Per Pallet 171

Case Weight 5.44 kg

I 2 of 5 Code 30078254920055 Appearance Amber Liquid

Base Type Petroleum Distillate

Flash point (F) >212°F Flash point (C) >100°C

Flammability Class - CPSC None (Under South Africa definitions)

Spec Gravity Concentrate 0.84
Plastic Safe Yes

Film Type Thin, Non-Drying
Film Thickness Not Determined

Last revised: 7/30/2019

Page 1 of 2





No Photo Available

Evaporation Rate Slow

Dielectric Strength 55,300 Volts
Working Temp (F) Max 250°F
Working Temp (C) Max 121.1°C
Propellant Carbon Dioxide

NSF Category Code H2

NSF Number 146293

Military Specification Not Determined

Number

Aerosol Flammability Level III

DOT Proper Shipping Name Aerosols, Non-Flammable, Limited Quantity

VOC % (Consumer Product 0

def)

VOC g/L (Consumer 0

Product def)

VOC lbs/gal (Consumer 0

Prod def)

VOC Category Not Regulated

Restricted from Sale In: Not for sale in United States.

Removal (How To) Remove with Petroleum Distillates.

Last revised: 7/30/2019

Page 2 of 2

