



1st Zinc® Primer Coat, 12.5 Wt OZ No. FZ-100 | Item# 1008303 | Case# 1008224

Product Description 95% pure zinc metal in traditional gray color. Meets or

exceeds requirements of ASTM-A780, DOD-P-21035A, Mil-

P-26915, Mil-P-46105.

Color Gray

Applications For parts and assemblies to be top-coated.

Unit Package Description 16 Ounce Aerosol

Brand Weld-Aid

Generic Description 1 Corrosion Inhibitor

Net Fill 12.5 Wt Oz

UPC Code 731592810011

Unit Dimensions 9.25H x 2.75W x 2.75D in

Units Per Case 12

Case Dimensions 8.75H x 8.25W x 11.00D in

Cases Per Pallet 64

Case Weight 14.40 lbs

I 2 of 5 Code 30731592810012

Appearance Gray Liquid

Flash point (F) -4°F

Flash point (C) -20°C

Flammability Class - CPSC Flammable Aerosol

Plastic Safe Not Determined

Evaporation Rate Moderate

pH Not Applicable

Dry Time - Fully Dry 24 Hours
Dry Time - Tack Free 15 Minutes

Recoat 15 Minutes

Coverage Not Determined

Dielectric Strength Not Determined

Last revised: 5/1/2020

Page 1 of 2







Working Temp (F)

Working Temp (C)

Propellant

Aerosol Flammability Level

Not Determined

Butane, Propane

Military Specification Mil-P-26915,Mil-P-46105,DOD-P-210352A Number

VOC % (Consumer Product 60.4 def)

VOC g/L (Consumer 592 Product def)

VOC lbs/gal (Consumer 4.93

Prod def)

VOC Category Aerosol Coating: Metallic Coating

MIR Limit (EPA) 1.9
MIR Limit (CA) 1.25
MIR Value 1.03

Removal (How To) Remove with paint stripper or other solvent.

Last revised: 5/1/2020

Page 2 of 2

