

1st Zinc® Gallon

No. FZ-200 | Item# 1008227

Product Description For parts and assemblies to be top-coated. 95% zinc

metal in traditional gray color. Meets or exceeds requirements of ASTM-A780, DOD-P-21035B; MIL-P-46105; MIL-P-26915B; SSPC PS-12; PS-20; PS-22; PS-29

& PS-30. Covers 570 square feet.

Color Gray

Applications For parts and assemblies to be top-coated.

Unit Package Description 1 Gallon Metal Pail

Brand Weld-Aid

Generic Description 1 Corrosion Inhibitor

Net Fill 1 Gal

UPC Code 731592820010

Unit Dimensions 12.5H x 6.5W X6.5D in

Units Per Case 1

Case Dimensions 12.5H x 6.5W X6.5D in

Cases Per Pallet 80

Case Weight 22 lbs

I 2 of 5 Code 30731592820011

Appearance Silver Liquid

Flash point (F) 45°F Flash point (C) 7.2°C Spec Gravity Concentrate 1.42

Plastic Safe Not Determined

Evaporation Rate Slow

Dry Time - Fully Dry 24 Hours

Dry Time - Tack Free 15 to 30 minutes at 70°F(21°C)

Recoat 15 to 30 Minutes

Coverage 570 square feet at 1 mil thickness (174m2)

Dielectric Strength Not Determined

Last revised: 9/15/2020

Page 1 of 2





Working Temp (F) Not Determined Working Temp (C) Not Determined

Propellant None

Aerosol Flammability Level Not Applicable

Military Specification MIL-P-26915B,Mil-P-46105 Number

DOT Proper Shipping Name Paint Related Materials, Limited Quantity

VOC Category Not Regulated - (Not for field application)

Last revised: 9/15/2020

Page 2 of 2

