



**1st Zinc® Gallon**  
 No. FZ-200 | Item# 1008227

Product Description	For parts and assemblies to be top-coated. 95% zinc metal in traditional gray color. Meets or exceeds requirements of ASTM-A780, DOD-P-21035B; MIL-P-46105; MIL-P-26915B; SSPC PS-12; PS-20; PS-22; PS-29 & PS-30. Covers 570 square feet.
Color	Gray
Applications	For parts and assemblies to be top-coated.
Unit Package Description	1 Gallon Metal Pail
Brand	Weld-Aid
Generic Description 1	Corrosion Inhibitor
Net Fill	1 Gal
UPC Code	731592820010
Unit Dimensions	12.5H x 6.5W X6.5D in
Units Per Case	1
Case Dimensions	12.5H x 6.5W X6.5D in
Cases Per Pallet	80
Case Weight	22 lbs
I 2 of 5 Code	30731592820011
Appearance	Silver Liquid
Flash point (F)	45°F
Flash point (C)	7.2°C
Spec Gravity Concentrate	1.42
Plastic Safe	Not Determined
Evaporation Rate	Slow
Dry Time - Fully Dry	24 Hours
Dry Time - Tack Free	15 to 30 minutes at 70°F(21°C)
Recoat	15 to 30 Minutes
Coverage	570 square feet at 1 mil thickness (174m2)
Dielectric Strength	Not Determined

Last revised: 9/15/2020  
 Page 1 of 2





Working Temp (F)	Not Determined
Working Temp (C)	Not Determined
Propellant	None
Aerosol Flammability Level	Not Applicable
Military Specification Number	MIL-P-26915B, Mil-P-46105
DOT Proper Shipping Name	Paint Related Materials, Limited Quantity
VOC Category	Not Regulated - (Not for field application)

Last revised: 9/15/2020  
Page 2 of 2