



Honing & Cutting Oil, 1 Gal

No. SL2523 | Item# 1007833 | Case# 1007832

Product Description An all-purpose metal working/ cutting lubricant that

extends tool life and improves machined surface finish.

Applications Valve refacing, piston pin fitting, honing, tapping,

reaming, grinding, threading, boring, broaching, drilling

and milling

Unit Package Description 1 Gallon Bottle

Brand Sta-Lube

Generic Description 1 Honing & Cutting Oil

Net Fill 1 Gal

UPC Code 072213252309

Unit Dimensions 10.63H x 4.75W x 6D in

Units Per Case 4

Case Dimensions 11.25H x 11.25W x 13.5D in

Cases Per Pallet 60

Case Weight 33 lbs

I 2 of 5 Code 30072213252300

Appearance Red Liquid
Flash point (F) 378°F
Flash point (C) 192°C
Flammability Class - CPSC None

Spec Gravity Concentrate 0.89

Plastic Safe Not Determined

Evaporation Rate Slow I SO Viscosity Grade 32

Working Temp (F) 50 to 150°F
Working Temp (C) 10 to 65.6°C
DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product 2.9

def)

Last revised: 2/10/2020

Page 1 of 2







VOC g/L (Consumer 26

Product def)

VOC lbs/gal (Consumer Prod def) 0.2

Cutting or Tapping Oil (Non-Aerosol) **VOC Category**

SCAQMD Restricted from Sale In:

Removal (How To) Remove with a general purpose degreaser

Last revised: 2/10/2020

Page 2 of 2

