



Hydraulic & Jack Oil, 32 Fl Oz

No. SL2552 | Item# 1007839 | Case# 1007838

Product Description	A medium weight hydraulic oil blended of a high quality paraffinic base oil with anti-rust, anti-oxidation, anti-foam, anti-wear, and seal swell additives. It is a 20W, non-detergent oil.
Applications	Hydraulic systems and fluid drive units. May be added to existing fluids. Not for use in hydraulic brakes.
Unit Package Description	1 Quart Bottle
Brand	Sta-Lube
Generic Description 1	Hydraulic & Jack Oil
Net Fill	32 Fl Oz
UPC Code	072213255201
Unit Dimensions	7.5H x 2.5W x 4.75D in
Units Per Case	12
Case Dimensions	8H x 10.25W x 16.5D in
Cases Per Pallet	91
Case Weight	25 lbs
I 2 of 5 Code	30072213255202
Appearance	Amber Viscous Liquid
Flash point (F)	380°F
Flash point (C)	193°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.87 to 0.89
Plastic Safe	Yes
Evaporation Rate	Slow
ISO Viscosity Grade	46
SAE Grade	20
Working Temp (F)	0 to 150°F
Working Temp (C)	-17.8 to 65.6°C
DOT Proper Shipping Name	Not Regulated

Last revised: 12/16/2020

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t+ y+ in+ 800-272-8963 • crcindustries.com



VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Not Regulated