



Hydraulic & Jack Oil, 5 Gal No. SL2555 | Item# 1007842

Product Description A medium weight hydraulic oil blended of a high quality

paraffinic base oil with anti-rust, anti-oxidation, anti-foam, anti-wear, and seal swell additives. It is a 20W, non-

detergent oil.

Hydraulic systems and fluid drive units. May be added to **Applications**

existing fluids. Not for use in hydraulic brakes.

Unit Package Description 5 Gallon Pail

Brand Sta-Lube

Generic Description 1 Hydraulic & Jack Oil

Net Fill 5 Gal

UPC Code 072213255508

Unit Dimensions 14.5H x 12W x 12D in

Units Per Case

Case Dimensions 14.5H x 12W x 12D in

Cases Per Pallet 36

Case Weight 45 lbs

Amber Viscous Liquid **Appearance**

380°F Flash point (F) 193°C Flash point (C) Flammability Class - CPSC None

Spec Gravity Concentrate 0.87 to 0.89

Plastic Safe Yes **Evaporation Rate** Slow **ISO Viscosity Grade** 46 to 68

SAE Grade 20

0 to 150°F Working Temp (F)

Working Temp (C) -17.78 to 65.56°C Not Regulated

DOT Proper Shipping Name

VOC % (Consumer Product

def)

Last revised: 12/16/2020

Page 1 of 2



0



0



VOC g/L (Consumer Product def) 0

VOC lbs/gal (Consumer Prod def)

VOC Category Not Regulated

Last revised: 12/16/2020

Page 2 of 2

