



## Hydraulic & Jack Oil, 15 Fl Oz

No. SL2621 | Item# 1007846 | Case# 1007845

Product Description A medium weight hydraulic oil blended of a high quality

paraffinic base oil with anti-rust, anti-oxidation, anti-foam, anti-wear, and seal swell additives. It is a 20W, non-

detergent oil.

Applications Hydraulic systems and fluid drive units. May be added to

existing fluids. Not for use in hydraulic brakes.

Unit Package Description 15 Ounce Bottle

Brand Sta-Lube

Generic Description 1 Hydraulic & Jack Oil

Net Fill 15 Fl Oz

UPC Code 072213262100

Unit Dimensions 9H x 1.63W x 3.75D in

Units Per Case 12

Case Dimensions 9.75H x 8.5W x 11.5D in

Cases Per Pallet 133
Case Weight 13 lbs

I 2 of 5 Code 30072213262101

Appearance Amber Viscous Liquid

Flash point (F) 380°F Flash point (C) 193°C Flammability Class - CPSC None

Spec Gravity Concentrate 0.87 to 0.89

Plastic Safe Yes
Evaporation Rate Slow
I SO Viscosity Grade 46
SAE Grade 20

Working Temp (F) 0 to 150°F

Working Temp (C) -17.78 to 65.56°C

DOT Proper Shipping Name Not Regulated

Last revised: 12/16/2020

Page 1 of 2







VOC % (Consumer Product 0 def)

VOC g/L (Consumer 0 Product def)

VOC lbs/gal (Consumer 0 Prod def)

VOC Category Not Regulated

Last revised: 12/16/2020

Page 2 of 2

