



Marine Boat Trailer and 4x4 Wheel Bearing Grease, 14 Wt Oz
 No. SL3121 | Item# 1007858 | Case# 1007857

Product Description	A blue tacky, aluminum complex grease using a highly refined base oil. It has been formulated with a polymer to provide adhesive, non-blend and water wash-out characteristics. Will resist water under the most severe water conditions.
Applications	Anti-friction bearings, blocks, boat trailer bearings, deck equipment, marine equipment, shaft log seals, sleeve bearings, slides, steering cables, steering dockside machinery, steering quadrants, turnbuckles, wheel bearings, winches
Unit Package Description	14 Ounce Can
Brand	Sta-Lube
Generic Description 1	Marine Grease for Boat Trailer
Net Fill	14 Wt Oz
UPC Code	072213312102
Unit Dimensions	3.44H x 4.13W x 4.13D in
Units Per Case	12
Case Dimensions	3.5H x 12.5W x 17D in
Cases Per Pallet	108
Case Weight	13 lbs
I 2 of 5 Code	30072213312103
Appearance	Blue Semi-Solid to Solid Grease
Base Type	Aluminum Complex
Flash point (F)	>450°F
Flash point (C)	>232.2°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.9
NLGI Grade	2
Plastic Safe	Not Determined
Evaporation Rate	Slow
Working Temp (F)	0 to 325°F

Last revised: 1/16/2019
 Page 1 of 2





Working Temp (C)	-17.8 to 162°C
Drop Point	500°F
Leakage	5
Oxidation Stability	5
Pour Point (F)	0°F
Pour Point (C)	-17.78°C
ISO Viscosity Grade	180 Cst at 40°C
Water Washout	5% at 175°F
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 1/16/2019
Page 2 of 2