



Marine Boat Trailer and 4x4 Wheel Bearing Grease, 35 Lbs No. SL3125 | Item# 1007859

Product Description A blue tacky, aluminum complex grease using a highly

refined base oil. It has been formulated with a polymer to

provide adhesive, non-blend and water wash-out characteristics. Will resist water under the most severe

water conditions.

Applications Anti-friction bearings, blocks, boat trailer bearings, deck

equipment, marine equipment, shaft log seals, sleeve bearings, slides, steering cables, steering dockside machinery, steering quadrants, turnbuckles, wheel

bearings, winches

Unit Package Description 35 Pound Pail

Brand Sta-Lube

Generic Description 1 Marine Grease for Boat Trailer

Net Fill 35 Lb

UPC Code 072213312508

Unit Dimensions 14.5H x 12W x 12D in

Units Per Case 1

Case Dimensions 14.5H x 12W x 12D in

Cases Per Pallet 36
Case Weight 41 lbs

Appearance Blue Semi-Solid to Solid Grease

Base Type Aluminum Complex

Flash point (F) $>450^{\circ}F$ Flash point (C) $>232.2^{\circ}C$

Flammability Class - CPSC None
Spec Gravity Concentrate 0.9
NLGI Grade 2

Plastic Safe Not Determined

Evaporation Rate Slow

Working Temp (F) 0 to 325°F

Working Temp (C) -17.8 to 162°C

Last revised: 1/16/2019

Page 1 of 2







Drop Point 500°F Leakage 5

Oxidation Stability 5
Pour Point (F) 0°F

Pour Point (C) -17.78°C

I SO Viscosity Grade 180 Cst at 40°C Water Washout 5% at 175°F Worked Penetration 265 to 295

Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product 0

def)

VOC g/L (Consumer 0

Product def)

VOC lbs/gal (Consumer 0

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

Last revised: 1/16/2019

Page 2 of 2

