



Heavy Duty Drum Brake Wheel Bearing Grease, 14 Wt Oz

No. SL3131 | Item# 1007862 | Case# 1007861

| | |
|---------------------------|--|
| Product Description | A sodium-based short fiber grease for autos & trucks with drum brake systems and slow speed industrial bearings. Meets most demands for economical wheel bearing lubrication. Good adhesive characteristics. |
| Applications | Drum brake systems, for use where heavy loads & slow speeds are present |
| Unit Package Description | 14 Ounce Can |
| Brand | Sta-Lube |
| Generic Description 1 | HD Drum Brake Wheel Bearing Grease |
| Net Fill | 14 Wt Oz |
| UPC Code | 072213313109 |
| Unit Dimensions | 3.44H x 4.13W x 4.13D in |
| Units Per Case | 12 |
| Case Dimensions | 3.5H x 12.5W x 17D in |
| Cases Per Pallet | 108 |
| Case Weight | 13 lbs |
| I 2 of 5 Code | 30072213313100 |
| Appearance | Dark Amber Semi-Solid to Solid Grease |
| Base Type | Sodium |
| Flash point (F) | 428°F |
| Flash point (C) | 220°C |
| Flammability Class - CPSC | None |
| Spec Gravity Concentrate | 0.9 at 60°F |
| NLGI Grade | 2.5 |
| Plastic Safe | Not Determined |
| Evaporation Rate | <0.01 (Butyl Acetate=1) |
| Working Temp (F) | 10 to 250°F |
| Working Temp (C) | -12.2 to 121.1°C |
| Drop Point | 360°F |

Last revised: 4/23/2019
Page 1 of 2





| | |
|---------------------------------|---|
| Leakage | Not Determined |
| Oil Separation | <10 |
| Oxidation Stability | 5 Lbs |
| Pour Point (F) | 10.4°F |
| Pour Point (C) | -17.78°C |
| ISO Viscosity Grade | 190 |
| Water Washout | Not Determined |
| Worked Penetration | 235 to 265 |
| Propellant | None |
| DOT Proper Shipping Name | Not Regulated |
| VOC % (Consumer Product def) | 0 |
| VOC g/L (Consumer Product def) | 0 |
| VOC lbs/gal (Consumer Prod def) | 0 |
| VOC Category | Not Regulated |
| Removal (How To) | Remove with a degreaser or brake cleaner product. |