



## Super White™ Multi-Purpose Lithium Grease, 400 Lbs No. SL3159 | Item# 1007877

Product Description A high purity, NLGI Grade 1.5 multi-purpose white lithium

grease. Provides superior lubrication & durability in any weather and most temperatures. Bright white in color.

Ideal for when appearance is important.

Applications Assembly lubes, bearings, break-in lubrication for

bearings, cables, chains, chassis points, conveyor bearings, door tracks, garage door channels & openers, hinges, latches, machinery, open gears, overhead door

tracks, roller bearings, sleeve bearings.

Unit Package Description 400 Pound Drum

Brand Sta-Lube

Generic Description 1 Super White Multi-Purpose Grease

Net Fill 400 Lb

UPC Code 072213315905

Unit Dimensions 35H x 23W x 23D in

Units Per Case 1

Case Dimensions 35H x 23W x 23D in

Cases Per Pallet 4

Case Weight 450 lbs

Appearance White Semi-Solid to Solid Grease

Base Type Lithium-12

Flash point (F) 475°F
Flash point (C) 246°C
Flammability Class - CPSC None

Spec Gravity Concentrate 0.9 at 60°F

NLGI Grade 1.5

Timken OK Load Lbs. 25 Lbs

Plastic Safe Not Determined

Evaporation Rate <0.01 (Butyl Acetate=1)

Working Temp (F) 0 to 300°F

Last revised: 7/30/2019

Page 1 of 2







Working Temp (C) -17.8 to 148.9°C

Drop Point 350°F

Leakage 5

Oil Separation 5

Oxidation Stability 10

Pour Point (F) 0°F

Pour Point (C) -17.78°C

ISO Viscosity Grade 165

Water Washout 10%

Worked Penetration 285 to 295

Propellant None

NSF Category Code H2

NSF Number 147593

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product < 0.1

def)

VOC g/L (Consumer < 0.9

Product def)

VOC lbs/gal (Consumer < 0.01

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

Last revised: 7/30/2019

Page 2 of 2

