



Hi Temperature Disc Brake Wheel Bearing Grease, 7 Lbs
 No. SL3166 | Item# 1007884 | Case# 1007883

Product Description	A very stable resistant Aluminum Complex grease. Contains rust & oxidation inhibitors, anti-wear and extreme pressure additives & fortified with "moly" and graphite. For use in automotive disc/drum brakes, chassis and suspension systems
Applications	Automotive applications, ball joints, bearings, chassis points, construction ball & roller bearings, conveyor bearings, disc-brake systems, farm equipment, guides, mining applications, press rolls, roller bearings, slides, wheel bearings
Unit Package Description	7 Pound Pail
Brand	Sta-Lube
Generic Description 1	Hi-Temp Disc Brake Wheel Grease
Net Fill	7 Lb
UPC Code	072213316605
Unit Dimensions	7.75H x 7.5W x 7.5D in
Units Per Case	4
Case Dimensions	8H x 16.5W x 16.5D in
Cases Per Pallet	54
Case Weight	33 lbs
I 2 of 5 Code	30072213316606
Appearance	Dark Gray Semi-Solid to Solid Grease
Base Type	Aluminum Complex
Flash point (F)	>450°F
Flash point (C)	>232°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.9 at 60°F
NLGI Grade	2
Timken OK Load Lbs.	60 Lbs
Plastic Safe	Not Determined
Evaporation Rate	<0.01 (Butyl Acetate=1)

Last revised: 4/23/2019
 Page 1 of 2





Working Temp (F)	0 to 325°F
Working Temp (C)	-18 to 162.5°C
4 Ball EP	30 LWI, 315 Kg Weld
4 Ball Wear	0.75 mm
Drop Point	500°F
Elastomer Compatibility	0 to 30% vol; 0 to 15 hard
Leakage	10g Max
Oil Separation	<10%
Oxidation Stability	2 to 3
Pour Point (F)	0°F
Pour Point (C)	-17.78°C
ISO Viscosity Grade	205
Water Washout	<15%
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0.4
VOC g/L (Consumer Product def)	3.6
VOC lbs/gal (Consumer Prod def)	0.03
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 4/23/2019
Page 2 of 2