



## Constant Velocity (CV) Joint Grease, 4 Wt Oz No. SL3174 | Item# 1007886 | Case# 1007885

Product Description A special lithium base grease fortified with molybdenum

disulfide and polymers. It is used for the installation & repair work on CV joints. Will extend the life of the CV joint & the additives will sustain the shock loads

encountered in the CV joints

Applications CV boot, CV joints found in front wheel drive passenger

vehicles, safe for both domestic & foreign CV joints

Unit Package Description 4 ounce Tube

Brand Sta-Lube

Generic Description 1 Constant Velocity Joint Grease

Net Fill 4 Wt Oz

UPC Code 072213317404

Unit Dimensions 9.25H x 4W x 1.5D in

Units Per Case 12

Case Dimensions 9.75H x 5.13W x 11D in

Cases Per Pallet 175
Case Weight 5 lbs

I 2 of 5 Code 30072213317405

Appearance Dark Gray Semi-Solid to Solid Grease

Base Type Lithium-12 Flash point (F)  $>450^{\circ}F$  Flash point (C)  $>232^{\circ}C$  Flammability Class - CPSC None

Spec Gravity Concentrate 0.9 at 60°F

NLGI Grade 1

Timken OK Load Lbs. 50 Lbs
Plastic Safe Yes

Evaporation Rate <0.01 (Butyl Acetate=1)

Working Temp (F)  $10 \text{ to } 275^{-}\text{F}$  Working Temp (C)  $-12.2 \text{ to } 134^{\circ}\text{C}$ 

Last revised: 4/23/2019

Page 1 of 2







4 Ball EP Not Determined
4 Ball Wear Not Determined

Drop Point 350°F

Elastomer Compatibility 0 to 40% vol; 0 to 15 hard

Leakage Not Determined

Oil Separation <10%
Oxidation Stability <5 Lbs
Pour Point (F) 10°F

Pour Point (C) -12.22°C

ISO Viscosity Grade 110

Water Washout Not Determined

Worked Penetration 300 to 330

Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product < 0.1

def)

VOC g/L (Consumer

Product def)

VOC lbs/gal (Consumer

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

< 0.9

< 0.007

Last revised: 4/23/2019

Page 2 of 2

