



Marine Boat Trailer and 4x4 Wheel Bearing Grease, 3 Wt Oz No. SL3184 | Item# 1007888 | Case# 1007887

Product Description A blue tacky, aluminum complex grease using a highly

refined base oil. It has been formulated with a polymer to

provide adhesive, non-blend and water wash-out characteristics. Will resist water under the most severe

water conditions.

Applications Anti-friction bearings, blocks, boat trailer bearings, deck

equipment, marine equipment, shaft log seals, sleeve bearings, slides, steering cables, steering dockside machinery, steering quadrants, turnbuckles, wheel

bearings, winches

Unit Package Description 3 Each 3 Ounce Cartridge

Brand Sta-Lube

Generic Description 1 Marine Grease for Boat Trailer

Net Fill 3 Wt Oz

UPC Code 072213318401

Unit Dimensions 8.5H x 6.25W x 1.5D in

Units Per Case 6

Case Dimensions 9H x 9.13W x 6.56D in

Cases Per Pallet 140
Case Weight 5 lbs

I 2 of 5 Code 30072213318402

Appearance Blue Semi-Solid to Solid Grease

Base Type Aluminum Complex

Flash point (F) $>450^{\circ}F$ Flash point (C) $>232.2^{\circ}C$

Flammability Class - CPSC None
Spec Gravity Concentrate 0.9
NLGI Grade 2

Plastic Safe Not Determined

Evaporation Rate Slow

Working Temp (F) 0 to 325°F

Last revised: 1/16/2019

Page 1 of 2







Working Temp (C) -17.8 to 162°C

Drop Point 500°F

Leakage 5

Oxidation Stability 5

Pour Point (F) 0°F

Pour Point (C) -17.78°C

ISO Viscosity Grade 180 Cst at 40°C

Water Washout 5% at 175°F

Worked Penetration 265 to 295

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product 0

def)

VOC g/L (Consumer 0

Product def)

Propellant

VOC lbs/gal (Consumer

Prod def)

VOC Category Not Regulated

Removal (How To)

Remove with a degreaser or brake cleaner product.

None

0

Last revised: 1/16/2019

Page 2 of 2

