



Sta-Lube Sta-Plex Premium Red Grease 1X11OZ

No. SL3192 | Item# 1007894 | Case# 1007893

Product Description

Premium red grease with heavy-duty lubricant that withstands high temperature and high pressure. Red color allows for easy visual inspection of film coverage.

Applications

Use on all types of high temperature, performance and heavy load applications. Electric motors, ball & roller bearings, industrial bearings, trucks, automobiles, buses, construction equipment, off-road operations, tractors, mowers, metal production, machining, assembly plants, striker plates, chains, cables, tools, linkages, conveyors, couplings, shovels, slides and more

Unit Package Description

16 Ounce Aerosol

Brand

Sta-Lube

Generic Description 1

Premium Red Grease

Net Fill

11 Wt Oz

UPC Code

072213319200

Unit Dimensions

7.75H x 2.63W x 2.63D in

Units Per Case

12

Case Dimensions

8.1H x 8.3W x 11.1D in

Cases Per Pallet

133

Case Weight

12 lbs

I 2 of 5 Code

30072213319201

Appearance

Red Viscous Grease

Base Type

Aluminum Complex

Flash point (F)

<23°F

Flash point (C)

<-5°C

Flammability Class - CPSC

Extremely Flammable

Spec Gravity Concentrate

0.72

NLGI Grade

2

Timken OK Load Lbs.

45

Plastic Safe

Yes

Evaporation Rate

Fast

Last revised: 7/29/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Dielectric Strength	Not Determined
Working Temp (F)	-25 to 300°F
Working Temp (C)	-31.7 to 148.9A°C
4 Ball EP	315
4 Ball Wear	0.6 mm
Drop Point	500°F
Leakage	5
Low Temp Torque	Not Determined
Oil Separation	Not Determined
Oxidation Stability	5
Pour Point (F)	0°F
Pour Point (C)	-17.78°C
Water Washout	Nil
Worked Penetration	265 to 295
Propellant	Hydrocarbon
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	63
VOC g/L (Consumer Product def)	453.6
VOC lbs/gal (Consumer Prod def)	3.78
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with Petroleum Distillates.

