



Lithium General Purpose Grease, 16 Wt Oz

No. SL3311 | Item# 1007906 | Case# 1007905

Product Description A high purity, NLGI Grade 2 lithium based grease.

Provides superior lubrication & durability in any weather and most temperatures. It is a versatile grease designed for light duty applications requiring a long grease life. Will

not break down or run out.

Applications Hinges, latches, overhead door tracks, open gears, chains,

cables, slide conveyors, guide rails, cams, pistons,

machinery, tools, & equipment. A break-in lubrication for

bearings.

Unit Package Description 16 Ounce Can

Brand Sta-Lube

Generic Description 1 Lithium General Purpose Grease

Net Fill 16 Wt Oz

UPC Code 072213331103

Unit Dimensions 3.44H x 4.13W x 4.13D in

Units Per Case 12

Case Dimensions 3.5H x 12.5W x 17D in

Cases Per Pallet 96
Case Weight 14 lbs

I 2 of 5 Code 30072213331104

Appearance Amber Semi-Solid to Solid Grease

Base Type Lithium-12

Flash point (F) 435°F
Flash point (C) 224°C
Flammability Class - CPSC None

Spec Gravity Concentrate 0.9 at 60°F

NLGI Grade 2

Timken OK Load Lbs. Not Determined
Plastic Safe Not Determined

Evaporation Rate Slow

Last revised: 5/14/2020

Page 1 of 2







Working Temp (F) 0 to 250°F

Working Temp (C) -17.8 to 121°C

4 Ball EP Not Determined

4 Ball Wear Not Determined

Drop Point 350°F

Leakage Not Determined

Oil Separation <10%

Oxidation Stability 5

Pour Point (F) -15°F
Pour Point (C) -26°C
I SO Viscosity Grade 150

Water Washout <15%

Worked Penetration 265 to 295

Propellant None

DOT Proper Shipping Name Not Regulated VOC % (Consumer Product Not Determined

def)

VOC g/L (Consumer Not Determined

Product def)

VOC lbs/gal (Consumer Not Determined

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

Last revised: 5/14/2020

Page 2 of 2

