



Lithium General Purpose Grease, 35 Lbs No. SL3315 | Item# 1007907

Product Description A high purity, NLGI Grade 2 lithium based grease.

Provides superior lubrication & durability in any weather and most temperatures. It is a versatile grease designed for light duty applications requiring a long grease life. Will

not break down or run out.

Applications Hinges, latches, overhead door tracks, open gears, chains,

cables, slide conveyors, guide rails, cams, pistons,

machinery, tools, & equipment. A break-in lubrication for

bearings.

Unit Package Description 35 Pound Pail

Brand Sta-Lube

Generic Description 1 Lithium General Purpose Grease

Net Fill 35 Lb

UPC Code 072213331509

Unit Dimensions 13.8H x 11.3W x 11.3D in

Units Per Case 1

Case Dimensions 13.8H x 11.3W x 11.3D in

Cases Per Pallet 36
Case Weight 40 lbs

Appearance Amber Semi-Solid to Solid Grease

Base Type Lithium-12
Flash point (F) 435°F
Flash point (C) 224°C
Flammability Class - CPSC None

Spec Gravity Concentrate 0.9 at 60°F

NLGI Grade 2

Timken OK Load Lbs. Not Determined
Plastic Safe Not Determined

Evaporation Rate Slow

Working Temp (F) 0 to 250°F

Last revised: 5/14/2020

Page 1 of 2







Working Temp (C) -18 to 121°C

4 Ball EP Not Determined

4 Ball Wear Not Determined

Drop Point 350°F

Elastomer Compatibility Not Determined
Leakage Not Determined
Low Temp Torque Not Determined

Oil Separation <10%

Oxidation Stability 5

Pour Point (F) -15°F

Pour Point (C) -26°C

I SO Viscosity Grade 150

Water Washout <15%

Worked Penetration 265 to 295

Propellant None

DOT Proper Shipping Name Not Regulated VOC % (Consumer Product Not Determined

def)

VOC g/L (Consumer Not Determined

Product def)

VOC lbs/gal (Consumer Not Determined

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

Last revised: 5/14/2020

Page 2 of 2

