



Extreme Pressure Engine Assembly Lube, 2.75 Wt Oz
 No. SL3333 | Item# 1007914 | Case# 1007913

Product Description	Engine Assembly lube is a lithium 12 hydroxy stearate based grease which adheres to metal surfaces to prevent destructive metal to metal contact. Prevents friction, galling and wear on all types of engines.
Applications	The assembly of all mechanical parts. Lubricating areas of rotation sliding contact, such as cylinders, crank shafts and cam shafts. Also recommended for coating internal engine parts during assembly
Unit Package Description	2.75 Ounce Tube
Brand	Sta-Lube
Generic Description 1	Anti-Seize Engine Assembly Lube
Net Fill	2.75 Wt Oz
UPC Code	072213333305
Unit Dimensions	8.5H x 5W x 1.5D in
Units Per Case	12
Case Dimensions	9.06H x 5.13W x 9D in
Cases Per Pallet	260
Case Weight	3 lbs
I 2 of 5 Code	30072213333306
Appearance	Black Semi-Solid to Solid Grease
Base Type	Lithium-12 Hydroxy
Flash point (F)	450°F
Flash point (C)	232°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.90
Plastic Safe	Yes
Evaporation Rate	Slow
ISO Viscosity Grade	230
NLGI Grade	0.5
Working Temp (F)	0 to 250°F



Last revised: 9/5/2019
 Page 1 of 2





Working Temp (C)	-17.78 to 121°C
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	<0.1
VOC g/L (Consumer Product def)	<0.9
VOC lbs/gal (Consumer Prod def)	<0.007
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 9/5/2019
Page 2 of 2