



Extreme Pressure Engine Assembly Lube, 2.75 Wt Oz No. SL3333 | Item# 1007914 | Case# 1007913

Product Description Engine Assembly lube is a lithium 12 hydroxy stearate

based grease which adheres to metal surfaces to prevent destructive metal to metal contact. Prevents friction,

galling and wear on all types of engines.

Applications The assembly of all mechanical parts. Lubricating areas of

rotation sliding contact, such as cylinders, crank shafts and cam shafts. Also recommended for coating internal

engine parts during assembly

Unit Package Description 2.75 Ounce Tube

Brand Sta-Lube

Generic Description 1 Anti-Seize Engine Assembly Lube

Net Fill 2.75 Wt Oz

UPC Code 072213333305

Unit Dimensions 8.5H x 5W x 1.5D in

Units Per Case 12

Case Dimensions 9.06H x 5.13W x 9D in

Cases Per Pallet 260
Case Weight 3 lbs

I 2 of 5 Code 300722133333306

Appearance Black Semi-Solid to Solid Grease

Base Type Lithium-12 Hydroxy

Flash point (F) 450°F 232°C Flash point (C) Flammability Class - CPSC None Spec Gravity Concentrate 0.90 Plastic Safe Yes **Evaporation Rate** Slow ISO Viscosity Grade 230 **NLGI** Grade 0.5

Working Temp (F) 0 to 250°F

Last revised: 9/5/2019

Page 1 of 2







Working Temp (C) -17.78 to 121°C

Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product < 0.1

def)

VOC g/L (Consumer < 0.9

Product def)

VOC lbs/gal (Consumer < 0.007

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

Last revised: 9/5/2019

Page 2 of 2

