



Super White™ Multi-Purpose Lithium Grease, 10 Wt Oz
 No. SL3360 | Item# 1007916 | Case# 1007915

Product Description	A high purity, NLGI Grade 2 multi-purpose white lithium grease. Provides superior lubrication & durability in any weather and most temperatures. Bright white in color. Ideal for when appearance is important.
Applications	Assembly lubes, bearings, break-in lubrication for bearings, cables, chains, chassis points, conveyor bearings, door tracks, garage door channels & openers, hinges, latches, machinery, open gears, overhead door tracks, roller bearings, sleeve bearings.
Unit Package Description	10 Ounce Tube
Brand	Sta-Lube
Generic Description 1	Super White Multi-Purpose Grease
Net Fill	10 Wt Oz
UPC Code	072213336009
Unit Dimensions	10H x 3W x 2D in
Units Per Case	6
Case Dimensions	4.13H x 6.75W x 10.25D in
Cases Per Pallet	250
Case Weight	5 lbs
I 2 of 5 Code	30072213336000
Appearance	White Semi-Solid to Solid Grease
Base Type	Lithium-12
Flash point (F)	475°F
Flash point (C)	246°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.9 at 60°F
NLGI Grade	2
Timken OK Load Lbs.	25 Lbs
Plastic Safe	Not Determined
Evaporation Rate	<0.01 (Butyl Acetate=1)

Last revised: 7/30/2019
 Page 1 of 2





Working Temp (F)	0 to 300°F
Working Temp (C)	-17.8 to 148.9°C
Drop Point	350°F
Leakage	5
Oil Separation	5
Oxidation Stability	10
Pour Point (F)	0°F
Pour Point (C)	-17.78°C
ISO Viscosity Grade	165
Water Washout	10
Worked Penetration	285 to 295
Propellant	None
NSF Category Code	H2
NSF Number	147593
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	<0.1
VOC g/L (Consumer Product def)	<0.9
VOC lbs/gal (Consumer Prod def)	<0.01
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 7/30/2019
Page 2 of 2