



Red Grease #2, 14 Wt Oz

No. SL3400 | Item# 1007920 | Case# 1007919

Product Description A multi-purpose lithium complex based NLGI #2 grease.

Contains extreme pressure, anti-wear, & anti-oxidation

additives. Drop point 540°F typical.

Applications Ind. mining, metal production, machining, plastic molding,

pumps, electric motors, ball & roller bearings, kilns, assembly plants, drying ovens, trucks, automobiles, buses, construction equipment, off-road operations,

tractors mowers, reapers, water pumps

Unit Package Description 14 Ounce Cartridge

Brand Sta-Lube

Generic Description 1 Red Grease #2

Net Fill 14 Wt Oz

UPC Code 072213340006

Unit Dimensions 9.31H x 2.13W x 2.13D in

Units Per Case 10

Case Dimensions 9.6H x 4.6W x 11D in

Cases Per Pallet 150
Case Weight 10 lbs

I 2 of 5 Code 30072213340007

Appearance Smooth, Tacky Red

Base Type Lithium Complex

Flash point (F) 450°F

Flash point (C) 232°C Flammability Class - CPSC None

Spec Gravity Concentrate 0.9
NLGI Grade 2

NLGI Grade 2
Timken OK Load Lbs. 60 Lbs

Plastic Safe Yes
Evaporation Rate Slow

Working Temp (F) -10 to 325°F

Last revised: 4/23/2019

Page 1 of 2







Working Temp (C) -12 to 162°C
4 Ball EP 250 Kg
4 Ball Wear 0.6 mm
Drop Point 540°F
Leakage 6
Low Temp Torque 15.5 Max

Oil Separation 3.5

Oxidation Stability 5

Pour Point (F) Not Determined

Water Washout 7

Worked Penetration 265 to 295

Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product 0

def)

VOC g/L (Consumer 0

Product def)

VOC lbs/gal (Consumer 0

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with a degreaser.

