

## Permatherm<sup>™</sup> High Temp Synthetic Grease, 35 Lbs (Discontinued)

No. SL3585 | Item# 1007934

Product

Discontinued

Product Description A high performance synthetic grease that incorporates a

non-melting thickener. Its proprietary chemistry provides

exceptional anti-wear properties up to 600 F.

Applications Clinker cooler bearings, fans, high temperature

applications, high temperature pumps, mining applications, ovens, overhead oven trolleys, paper machine dryers, pumps, super heated steam dryers,

treadmills

Unit Package Description 35 Pound Pail

Brand Sta-Lube

Generic Description 1 High Temp Synthetic Grease

Net Fill 35 Lb

UPC Code 072213358506

Unit Dimensions 14.5H x 12W x 12D in

Units Per Case 1

Case Dimensions 14.5H x 12W x 12D in

Cases Per Pallet 36
Case Weight 40 lbs

Appearance Amber Semi-Solid to Solid Grease

Base Type Fumed Silica

Flash point (F) 500°F
Flash point (C) 260°C
Flammability Class - CPSC None

Spec Gravity Concentrate 0.9 at 60°F

NLGI Grade 1.5

Timken OK Load Lbs. 50 Lbs

Plastic Safe Not Determined

Evaporation Rate <1 (butyl acetate=1)

Working Temp (F) -40 to 400°F

Last revised: 5/21/2019

Page 1 of 2





## Product Discontinued

Working Temp (C) -40 to 204°C 4 Ball EP Not Determined

4 Ball Wear 0.5 mm
Drop Point 600°F

Leakage Not Determined

Oil Separation 1%
Oxidation Stability 5

Pour Point (F) Not Determined
Pour Point (C) Not Determined

I SO Viscosity Grade 450 Water Washout <5

Worked Penetration 275 to 305

Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product < 0.1

def)

VOC g/L (Consumer

Product def)

VOC lbs/gal (Consumer <0.007

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

< 0.9

Last revised: 5/21/2019

Page 2 of 2

