



**Lectra Lube™ Electric Motor Grease, 14 Wt Oz**  
 No. SL3586 | Item# 1007936 | Case# 1007935

Product Description	A premium long-life grease with excellent thermal stability. This grease has excellent water resistance and will not washout. It maintains its consistency under severe working conditions and resists oxidation.
Applications	"Sealed for Life" bearings and motors
Unit Package Description	14 Ounce Cartridge
Brand	CRC
Generic Description 1	Polyurea Thickened NLGI 2 Grease
Net Fill	14 Wt Oz
UPC Code	072213358605
Unit Dimensions	9.31H x 2.13W x 2.13D in
Units Per Case	10
Case Dimensions	9.5H x 4.5W x 11.38D in
Cases Per Pallet	150
Case Weight	11 lbs
I 2 of 5 Code	30072213358606
Appearance	Blue Green Solid Grease
Base Type	Polyurea
Flash point (F)	400°F
Flash point (C)	204°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.87
NLGI Grade	2
Timken OK Load Lbs.	50 Lbs
Plastic Safe	Not Determined
Evaporation Rate	Slow
Working Temp (F)	0 to 400°F
Working Temp (C)	-18 to 204°C
4 Ball EP	400 Kg min

Last revised: 4/10/2018  
 Page 1 of 2





4 Ball Wear	0.65 mm
Drop Point	500°F
Water Washout	5% Max at 175°F
Worked Penetration	265
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	1
VOC g/L (Consumer Product def)	8.7
VOC lbs/gal (Consumer Prod def)	0.07
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.