



Nickel Anti-Seize Lubricating Compound, 8 Wt Oz

No. SL35911 | Item# 1007946 | Case# 1007945



| | |
|---------------------------|--|
| Product Description | Sta-Lube Nickel Anti-Seize is a nickel based formula that is free of copper, lead, sulfides and chlorides. This premium quality lubricant has excellent high temperature and chemical resistance. Conductive. |
| Applications | Catalyst beds, reaction chambers, special alloy fittings. May be used on fittings, bushings, flanges, headers, nuts, screws, studs, threaded surfaces, pipes, plugs, and manifolds to prevent seizing and galling of surfaces. |
| Unit Package Description | 8 Ounce Brush-Top Bottle |
| Brand | CRC |
| Generic Description 1 | General Purpose Anti Seize Lubricant |
| Net Fill | 8 Wt Oz |
| UPC Code | 072213359114 |
| Unit Dimensions | 4.25H x 2.5W x 2.5D in |
| Units Per Case | 12 |
| Case Dimensions | 5H x 10.0W x 6.63D in |
| Cases Per Pallet | 108 |
| Case Weight | 8 lbs |
| I 2 of 5 Code | 30072213359115 |
| Appearance | Silver Paste |
| Base Type | Nickel |
| Flash point (F) | 425°F |
| Flash point (C) | 218°C |
| Flammability Class - CPSC | Not Applicable |
| Spec Gravity Concentrate | 1.18 |
| Plastic Safe | Yes |
| Film Type | Wet |
| Evaporation Rate | Not Applicable |
| Dielectric Strength | Not Determined |
| ISO Viscosity Grade | Not Applicable |

Last revised: 2/10/2020
Page 1 of 2





| | |
|---------------------------------|--|
| NLGI Grade | 1 |
| Working Temp (F) | -95 to 2600°F |
| Working Temp (C) | -70.6 to 1427°C |
| Propellant | None |
| Military Specification Number | Meets requirements of Mil-PRF-907E |
| Aerosol Flammability Level | Not Applicable |
| DOT Proper Shipping Name | Not Regulated |
| VOC % (Consumer Product def) | 1.8 |
| VOC g/L (Consumer Product def) | 21.2 |
| VOC lbs/gal (Consumer Prod def) | 0.18 |
| VOC Category | Anti-Seize Lubricant (Non-Aerosol) |
| Removal (How To) | Remove with general purpose degreaser. |