



Thread Lubricant, 2 Wt Oz

No. SL35924 | Item# 1007953 | Case# 1007952

Product Description	A general purpose lubricant that prevents the seizing and galling of threaded surfaces caused by corrosion. Safe for use on ferrous and non-ferrous metals.
Applications	For use on aluminum conduit, bolts, bushings, fittings, flanges, nuts, pipes, plugs and screws.
Unit Package Description	2 Ounce Tube
Brand	Sta-Lube
Generic Description 1	Thread Lubricant
Net Fill	2 Wt Oz
UPC Code	072213359244
Unit Dimensions	5.25H x 2.25W x 1.5D in
Units Per Case	50
Case Dimensions	8.75H x 11.75W x 13D in
Cases Per Pallet	36
Case Weight	9 lbs
I 2 of 5 Code	30072213359245
Appearance	Amber Semi-Solid to Solid Grease
Base Type	Lithium-12
Flash point (F)	334°F
Flash point (C)	168°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.90
Plastic Safe	Not Determined
Film Type	Grease
Evaporation Rate	Very Slow
ISO Viscosity Grade	150
NLGI Grade	2
Working Temp (F)	-20 to 250°F
Working Temp (C)	-17.8 to 148.9°C

Last revised: 10/3/2018
Page 1 of 2





Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	<0.1
VOC g/L (Consumer Product def)	<0.9
VOC lbs/gal (Consumer Prod def)	<0.01
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.