



## Thread Lubricant, 2 Wt Oz

No. SL35924 | Item# 1007953 | Case# 1007952

Product Description A general purpose lubricant that prevents the seizing and

galling of threaded surfaces caused by corrosion. Safe for

use on ferrous and non-ferrous metals.

Applications For use on aluminum conduit, bolts, bushings, fittings,

flanges, nuts, pipes, plugs and screws.

Unit Package Description 2 Ounce Tube

Brand Sta-Lube

Generic Description 1 Thread Lubricant

Net Fill 2 Wt Oz

UPC Code 072213359244

Unit Dimensions 5.25H x 2.25W x 1.5D in

Units Per Case 50

Case Dimensions 8.75H x 11.75W x 13D in

Cases Per Pallet 36
Case Weight 9 lbs

I 2 of 5 Code 30072213359245

Appearance Amber Semi-Solid to Solid Grease

Base Type Lithium-12

Flash point (F) 334°F
Flash point (C) 168°C
Flammability Class - CPSC None
Spec Gravity Concentrate 0.90

Plastic Safe Not Determined

Film Type Grease

Evaporation Rate Very Slow

I SO Viscosity Grade 150 NLGI Grade 2

Working Temp (F) -20 to 250°F

Working Temp (C) -17.8 to 148.9°C

Last revised: 10/3/2018

Page 1 of 2







Propellant None

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product < 0.1 def)

uci)

VOC g/L (Consumer <0.9 Product def)

VOC lbs /gal (Cons

VOC lbs/gal (Consumer < 0.01

Prod def)

VOC Category Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

Last revised: 10/3/2018

Page 2 of 2

