



Thread Lubricant, 8 Wt Oz

No. SL35925 | Item# 1007955 | Case# 1007944

Product Description	A general purpose lubricant that prevents the seizing and galling of threaded surfaces caused by corrosion. Safe for use on ferrous and non-ferrous metals.
Applications	For use on aluminum conduit, bolts, bushings, fittings, flanges, nuts, pipes, plugs and screws.
Unit Package Description	8 Ounce Bottle
Brand	Sta-Lube
Generic Description 1	Thread Lubricant
Net Fill	8 Wt Oz
UPC Code	072213359251
Unit Dimensions	4.25H x 2.5W x 2.5D in
Units Per Case	6
Case Dimensions	4.9H x 4.3W x 7.25D in
Cases Per Pallet	315
Case Weight	4 lbs
I 2 of 5 Code	30072213359252
Appearance	Amber Semi-Solid to Solid Grease
Base Type	Lithium-12
Flash point (F)	334°F
Flash point (C)	168°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.90
Plastic Safe	Not Determined
Film Type	Grease
Evaporation Rate	Very Slow
ISO Viscosity Grade	150
NLGI Grade	2
Working Temp (F)	-20 to 250°F
Working Temp (C)	-17.8 to 148.9°C

Last revised: 10/3/2018
Page 1 of 2





Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	<0.1
VOC g/L (Consumer Product def)	<0.9
VOC lbs/gal (Consumer Prod def)	<0.01
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.