



## Thread Lubricant, 8 Wt Oz

No. SL35925 | Item# 1007955 | Case# 1007944

|                           |   |
|---------------------------|---|
| Product Description       | A general purpose lubricant that prevents the seizing and galling of threaded surfaces caused by corrosion. Safe for use on ferrous and non-ferrous metals. |
| Applications              | For use on aluminum conduit, bolts, bushings, fittings, flanges, nuts, pipes, plugs and screws.   |
| Unit Package Description  | 8 Ounce Bottle  |
| Brand                     | Sta-Lube  |
| Generic Description 1     | Thread Lubricant  |
| Net Fill                  | 8 Wt Oz   |
| UPC Code                  | 072213359251  |
| Unit Dimensions           | 4.25H x 2.5W x 2.5D in  |
| Units Per Case            | 6   |
| Case Dimensions           | 4.9H x 4.3W x 7.25D in  |
| Cases Per Pallet          | 315   |
| Case Weight               | 4 lbs   |
| I 2 of 5 Code             | 30072213359252  |
| Appearance                | Amber Semi-Solid to Solid Grease  |
| Base Type                 | Lithium-12  |
| Flash point (F)           | 334°F   |
| Flash point (C)           | 168°C   |
| Flammability Class - CPSC | None  |
| Spec Gravity Concentrate  | 0.90  |
| Plastic Safe              | Not Determined  |
| Film Type                 | Grease  |
| Evaporation Rate          | Very Slow   |
| ISO Viscosity Grade       | 150   |
| NLGI Grade                | 2   |
| Working Temp (F)          | -20 to 250°F  |
| Working Temp (C)          | -17.8 to 148.9°C  |

Last revised: 10/3/2018  
Page 1 of 2





|                                 |   |
|---------------------------------|---|
| Propellant                      | None  |
| DOT Proper Shipping Name        | Not Regulated                                     |
| VOC % (Consumer Product def)    | <0.1  |
| VOC g/L (Consumer Product def)  | <0.9  |
| VOC lbs/gal (Consumer Prod def) | <0.01   |
| VOC Category                    | Not Regulated                                     |
| Removal (How To)                | Remove with a degreaser or brake cleaner product. |

Last revised: 10/3/2018  
Page 2 of 2