



Ball & Roller Bearing Hi-Temp Industrial Grease, 14 Wt Oz
 No. SL3630 | Item# 1007957 | Case# 1007956

Product Description	A special blend of treated petroleum base stocks, rust & oxidation inhibitors, extreme pressure additives combined with an aluminum complex thickener. It will not wash out, splatter or run out under severe loads. Friction and wear are greatly reduced.
Applications	Ball & Roller bearings, cement equipment, chassis points, construction applications, disc brake wheel bearings, heavy duty truck bearings, heavy loaded bushings, ideal for apps operating at intermittent temps up to 400 F, paper mills, steel mills
Unit Package Description	14 Ounce Cartridge
Brand	Sta-Lube
Generic Description 1	Ball & Roller Bearing Grease
Net Fill	14 Wt Oz
UPC Code	072213363005
Unit Dimensions	9.31H x 2.13W x 2.13D in
Units Per Case	10
Case Dimensions	9.5H x 4.5W x 11.38D in
Cases Per Pallet	150
Case Weight	11 lbs
I 2 of 5 Code	30072213363006
Appearance	Dark Gray Semi-Solid to Solid Grease
Base Type	Aluminum Complex
Flash point (F)	400°F
Flash point (C)	204°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.9 at 60°F
NLGI Grade	2
Timken OK Load Lbs.	40 Lbs
Plastic Safe	Not Determined
Evaporation Rate	<0.01 (Butyl Acetate=1)

Last revised: 4/23/2019
 Page 1 of 2





Working Temp (F)	0 to 325°F
Working Temp (C)	-18 to 162°C
4 Ball EP	58 LWI, 250 KG Weld
4 Ball Wear	0.9 mm max
Drop Point	485°F
Oil Separation	<10%
Oxidation Stability	5
Pour Point (F)	15°F
Pour Point (C)	-9.44°C
ISO Viscosity Grade	575
Water Washout	0.3
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0.3
VOC g/L (Consumer Product def)	2.7
VOC lbs/gal (Consumer Prod def)	0.022
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 4/23/2019
Page 2 of 2

