



Driller Red Grease Extreme Pressure Lithium Complex Grease, 35 Lbs No. SL3650 | Item# 1007960

| Product Description | Driller Red Grease is a NLGI #2 Red Grease which offer superior protection to lubricate a wide variety of severe duty drilling, industrial, mining and construction equipment. Timken load of 80 lbs. |
|---------------------------|---|
| Applications | Drilling and Mining applications, backing plates, ball joints, chassis points, construction ball & roller bearings, idler bearings, industrial applications, pillow block bearings, sprocket bearings, U-joints, water pumps, wheel bearings |
| Unit Package Description | 35 Pound Pail |
| Brand | CRC |
| Generic Description 1 | Extreme Pressure Lithium Complex Grease |
| Net Fill | 35 Lb |
| UPC Code | 072213365009 |
| Unit Dimensions | 15H x 12W x 12D in |
| Units Per Case | 1 |
| Case Dimensions | 15H x 12W x 12D in |
| Cases Per Pallet | 36 |
| Case Weight | 40 lbs |
| I 2 of 5 Code | 30072213365000 |
| Appearance | Red, Smooth, Tacky |
| Base Type | Lithium Complex |
| Flash point (F) | 302°F |
| Flash point (C) | 150°C |
| Flammability Class - CPSC | None |
| Spec Gravity Concentrate | 0.93 |
| NLGI Grade | 2 |
| Timken OK Load Lbs. | 80 Lbs |
| Plastic Safe | Yes |
| Dielectric Strength | Not Determined |

Last revised: 9/4/2019 Page 1 of 2

CRC

Chemical Solutions to Keep You Moving™ € ♥ ♥ ⊕ • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.



CRC

| Working Temp (F) | -10 to 400°F |
|------------------------------------|--------------------------|
| Working Temp (C) | -23 to 204°C |
| 4 Ball EP | 315 Kgf |
| 4 Ball Wear | 0.45 |
| Drop Point | 550°F |
| Leakage | 2.0 |
| Low Temp Torque | Not Determined |
| Oil Separation | 1.0 |
| Oxidation Stability | Not Determined |
| Pour Point (F) | Not Determined |
| Pour Point (C) | Not Determined |
| Water Washout | 2.5 at 175°F |
| Worked Penetration | 265 to 295 |
| Propellant | None |
| DOT Proper Shipping Name | Not Regulated |
| VOC % (Consumer Product def) | Not Determined |
| VOC g/L (Consumer Product def) | Not Determined |
| VOC lbs/gal (Consumer Prod def) | Not Determined |
| VOC Category | Not Regulated |
| Removal (How To) | Remove with a degreaser. |

Last revised: 9/4/2019

Page 2 of 2



CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.